




# CURRENT TRANSFORMERS TOROIDAL / THRU-HOLE



MYRRA Part N°	Sec. Turns	Max Pri. Current A rms	Rsec. $\Omega$ max	Lsec. mH min	Pulse Vsec x t max @ Frequency	Sine Vsec max @ Frequency	Typical Load/ Accuracy/ Current
74540	100	200 A	0.35 $\Omega$	50	2 V.ms/ 20 kHz 1 V.ms/ 100 kHz	150 V/ 20 kHz 150 V/ 100 kHz	1..20 $\Omega$ / 1%
74543	500	100 A	6.5 $\Omega$	1250	10 V.ms/ 50 Hz	0.7 V/ 50Hz/ 100 A 1.2 V/ 50Hz/ 60 A	$\leq$ 3 $\Omega$ / 1% / 100 A $\leq$ 10 $\Omega$ / 1% / 60 A
74546	1000	250 A	22 $\Omega$	8000	100 V.ms/ 50 Hz	15 V/ 50 Hz/ 250 A	$\leq$ 50 $\Omega$ / 1% / 250 A

Data applies for one primary turn (single passage of primary wire through toroid hole). Sensitivity can be increased for lower currents by winding more than one turn.

## 74540/ 74543/ 74546 Pin type (for PCB)

